

Page 1/8

Safety Data Sheet according to 1907/2006/EC, Article 31

Printing date 05.04.2016 Revision: 05.04.2016

1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: Kapci 1K Filler
- · Article number: 1K
- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture .
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Kapci Coatings

Industrial Zone El - Raswa

Port Said

EGYPT

info@kapci.com

- · Further information obtainable from: Product safety department
- · Emergency telephone number: During normal opening times: +20 66 3770000

2 Hazards identification

- · Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

· Hazard pictograms

(Contd. of page 1)







GHS02 GHS07 G

- · Signal word Danger
- · Hazard-determining components of labelling:

toluene

· Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterisation: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous compone	nts:	
0.10.10000	toluene	10-25%
EINECS: 203-625-9	🅎 Flam. Liq. 2, H225; 🕸 Repr. 2, H361d; STOT RE 2, H373; Asp. Tox. 1, H304; 🐧 Skin Irrit. 2, H315; STOT SE 3, H336	
		2.5-10%
EINECS: 204-658-1	🍅 Flam. Liq. 3, H226; 💠 STOT SE 3, H336	
CAS: 78-93-3	***********	2.5-10%
EINECS: 201-159-0	🊸 Flam. Liq. 2, H225; <page-header> Eye Irrit. 2, H319; STOT SE 3, H336</page-header>	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 3)

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

(Contd. of page 2)

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

GE

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

(Contd. of page 3)

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm Long-term value: 600 mg/m³, 200 ppm Sk, BMGV

· Ingredients with biological limit values:

78-93-3 butanone

BMGV 70 µmol/L Medium: urine

Sampling time: post shift Parameter: butan-2-one

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material


The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

 \cdot Eye protection:



(Contd. of page 4)

9 Physical and chemical proper	rties
· Information on basic physical and	chomical properties
General Information	chemical properties
· Appearance:	
Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	79 °C
· Flash point:	-4 °C
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	370 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.5 Vol %
· Vapour pressure at 20 °C:	29 hPa
· Density:	Not determined.
· Relative density	Not determined.
Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	35.0 %
VOC (EC)	35.00 %
Solids content:	65.0 %
· Other information	No further relevant information available.

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
108-88-3 t	oluene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

· STOT-single exposure

May cause drowsiness or dizziness.

· STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

· Aspiration hazard

May be fatal if swallowed and enters airways.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

 $\cdot \textit{Other adverse effects} \ \textit{No further relevant information available}.$

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, IMDG, IATA	UN1263
UN proper shipping name	
ADR	1263 PAINT
IMDG	PAINT
IATA	Paint
Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3 Transmatte inquitas.
Packing group	
ADR, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids.
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u>
Stowage Category	В
Transport in bulk according to Annex II	
and the IBC Code	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

Printing date 05.04.2016 Revision: 05.04.2016

Trade name: Kapci 1K Filler

(Contd. of page 7)

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

- · Department issuing SDS: Product safety department
- · Contact: Mr. Rashad
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

 $CAS:\ Chemical\ Abstracts\ Service\ (division\ of\ the\ American\ Chemical\ Society)$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Repr. 2: Reproductive toxicity, Hazard Category 2

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1